

CS22 D Transmitter

For monitoring toxic and flammable gases



CS22 D Transmitter

For monitoring toxic and flammable gases, with display and alarm

Wherever toxic or flammable gases and vapors must be monitored without requirements for explosion protection, the use of the CS22 D transmitter is recommended.

Proven and cost-effective

The CS22 D works on the principle of chemisorption (CS). Thanks to a wide range of monitorable gases and multiple measurement ranges, the CS22 D offers a wide range of uses, from laboratories to industrial applications to refrigeration systems.

Transmitters with electrochemical sensors (EC), are also used with toxic and flammable gases. In contrast, the CS22 D is a much more durable and cost-efficient solution. However, the environmental parameters must fit.

Analog and digital communication

The measured values and status information of the CS22 D can be transmitted either analog (4-20 mA or 0.2-1 mA) or digital (RS-485). This allows not only the use in combination with any GfG controller, but also the connection to programmable logic controllers (PLC).

Display and alarm on site

The D version of the CS22 has a 2.2 inch display to show measured values, status information and alarms at the measuring point. Normally backlit in green, the display changes for visual alert to red in the event of an alarm. At the same time, an acoustic alarm signal can be emitted from the integrated horn.

In combination with GfG's powerful controllers, the CS22 is the right choice for monitoring a wide range of gases.



CS22 D - durable and efficient

Overview of the gases and measuring ranges:

Other gases on request.

» n-Hexane	0 to 100 % LEL	» R-404A	0 to 1,000 ppm	» R-454B	0 to 1,000 ppm
» R-23	0 to 1,000 ppm		0 to 2,000 ppm		0 to 2,000 ppm
» R-1234yf	0 to 1,000 ppm	» R-407C	0 to 1,000 ppm	» R-507[A]	0 to 1,000 ppm
» R-1234ze	0 to 1,000 ppm	» R-410A	0 to 1,000 ppm	» R-717	0 to 300 ppm
» R-134a	0 to 1,000 ppm	» R-438A	0 to 1,000 ppm	(ammonia)	0 to 1,000 ppm
	0 to 2,000 ppm	» R-448A	0 to 1,000 ppm		0 to 3,000 ppm
	0 to 5,000 ppm	» R-449A	0 to 1,000 ppm		0 to 1,000 % by volume

Technical Data: CS22 D

Measuring principle: Chemisorption (CS)

Detection range*: 0-100% LEL

0-5,000 ppm

0-1,000% by volume

Gas supply: Diffusion or gassing per calibration adapter

Expected sensor life: Greater than 5 years

Response time: $t_{90} < 15$ s

Temperature: -4 to +122 °F /
-20 to +50 °C

Humidity: 5 to 90% r.h.

Pressure: 80 to 120 kPa

Output signal:

Analog: 0.2-1 mA or 4-20 mA

Digital: RS-485

Power supply: 12 to 30 V DC

Housing: Plastic

Protection class: IP54

Dimensions: 3.78 x 5.5 x 1.93 in /

96 x 140 x 49 mm (W x H x D)

Weight: 7.8 oz / 220 g

Approvals / Certifications:

Functional Safety (SIL):

DIN EN 61508-2: 2011

* Sensor dependent



www.gfgsafety.com/us-en

© GfG Instrumentation, Inc. 2022
All specifications on this brochure are subject to technical changes due to further development.

USA and Canada
Latin America
Germany
South Africa
Asia Pacific
Great Britain
Switzerland
France
Poland
Austria
Netherlands

info@goodforgas.com
info@goodforgas.com
info@gfg-mbh.com
info@gfg.co.za
sales@gfg-asiapac.sg
sales@gfggas.co.uk
info@gfg.ch
alainflachon@gfg-gasdetection.fr
biuro@gfg.pl
austria@gfg-mbh.com
info@gfg-gasdetection.nl



smart
GasDetection
Technologies **GfG**

GfG Instrumentation, Inc.

1194 Oak Valley Drive, Suite 20, Ann Arbor, MI 48108 USA
Phone: (734) 769-0573 • Toll Free (USA / Canada): (800) 959-0329
Website: www.gfgsafety.com/us-en • info@goodforgas.com

Rev. 1 (12/01/22)