



Dynagard 25 Series O₂

Single point fixed oxygen monitoring system



Dynagard 25 Series O₂

Single point fixed oxygen monitoring system

Simple and effective

The Dynagard 25 Series accurately measures oxygen levels. The unit offers a local display, a horn / strobe, and a linear 4-20 mA output. The Dynagard 25 Series offers a safe and reliable gas warning system.

Alarm points

Each alarm can be adjusted separately. The alarm point values can be freely adjusted within the detection range of the transmitter. Every alarm point value can be set to over range / under range, latching / non-latching, or resettable / non-resettable.

Alarm relays

The controller provides four voltage-free relays for the three alarms and one fault warning. The relays may be used to control additional alarm devices like lights or horns. They can even prompt specific counter measures to prevent or limit dangers from gases or vapors.

ZD21 zirconia sensor

The comprehensive electronics allow for easy operation and maintenance and also increase operational safety and accuracy. In less than 2 seconds, the ZD21 responds to an oxygen deficiency. The sensor has a platinum coating on the inside and outside of the ceramic cylinder. Oxygen is electrochemically reduced at the cathode.

The voltage produced is proportional to the net difference in the partial pressures of oxygen in the reference gas versus the sampled gas. This extremely short response time allows the user the time to take measures to prevent considerable damage.

Technical Data: Dynagard 25 Series O₂

Gas: Oxygen (O₂)

Detection range: 0-25% volume

Measuring principle: Zirconia oxide (ZD)

Gas supply: Diffusion

Expected sensor life: Greater than 5 years

Temperature: +32 to +122 °F / 0 to +55 °C

Humidity: 0 to 99% r.h. non-condensing

Pressure: 920 to 1,100 hPA

Output signal: Linear 4-20 mA

Power supply: 24 V DC wall pack

Display: 3-digit LED display for linear measurement values, service
1 LED green – operational status
1 LED yellow – fault
3 LEDs red – alarm
Display of max / min values

Horn: Low - 70 dB at 10 ft per UL 464

High - 83 dB at 10 ft per UL 464

Strobe: Light output on axis (cd)

Low - 35

High - 68

Alarms: 3 alarm points, user adjustable within the detection range

Alarm functions available:

Latching / non-latching
Resettable / non-resettable
Hysteresis adjustable
Delay-time 0 to 2 minutes
Alarm thresholds adjustable

Relays:

3 alarm points, 1 fault – voltage free

Factory settings

A1 - strobe

A2 - open

A3 - horn

Fault - open

Voltage: 250 V AC 50/60 Hz or
250 V DC maximum

Dimensions: 11 x 7 x 2.75 in /
27.9 x 17.8 x 7 cm
(H x W x D)

Weight: 6.5 lbs / 2.95 kg



www.gfgsafety.com/us-en

© GfG Instrumentation, Inc. 2022
All specifications on this brochure are subject to technical changes due to further development.

USA and Canada
Latin America
Germany
South Africa
Asia Pacific
Great Britain
Switzerland
France
Poland
Austria
Netherlands

info@goodforgas.com
info@goodforgas.com
info@gfg-mbh.com
info@gfg.co.za
sales@gfg-asiapac.sg
sales@gfggas.co.uk
info@gfg.ch
alainflachon@gfg-gasdetection.fr
biuro@gfg.pl
austria@gfg-mbh.com
info@gfg-gasdetection.nl

smart
GasDetection
Technologies 

GfG Instrumentation, Inc.

1194 Oak Valley Drive, Suite 20, Ann Arbor, MI 48108 USA
Phone: (734) 769-0573 • Toll Free (USA / Canada): (800) 959-0329
Website: www.gfgsafety.com/us-en • info@goodforgas.com

Rev. 1 (12/01/22)