



Portable Gas Detectors

smart  
**GasDetection**  
Technologies



# G222E

**Sturdy and compact dual gas detector for toxic gases, H<sub>2</sub> and O<sub>2</sub>**



[GfGsafety.com/us-en](http://GfGsafety.com/us-en)



# G222E Micro 5

Sturdy and compact dual gas detector for monitoring toxic gases, H<sub>2</sub> and O<sub>2</sub>

The G222E is the first device in GfG’s Micro 5 series. At present, it is the smallest and at the same time one of the lightest one- to two-gas detectors with two electrochemical gas sensors (EC) in the world.

**Safety through quality and functionality**

Equipped with high-quality, precise and durable sensors, the system is individually tailored to your requirements. Currently, sensors are available for 20 different gases and a wide array of measuring ranges. Combine them according to your requirements or increase the safety of your employees even further by redundant use of the same sensors to minimize the danger from a specific gas.

A simple, two-button menu and a large, easy-to-read display provide easy menu navigation and reliable information even under difficult conditions.

*Size comparison between the G222 and the G999 multi-gas detector.*



### Suitable for long periods of use

Depending on sensor equipment and configuration, the G222E has an average operating time of up to 9 months at 10 hours per working day or 90 days in 24/7 operation. The battery of the G222E can be changed in seconds if necessary and the gas detector is ready for use again.

### Data logger

The internal data logger stores the last 2600 events. These include measured values, alarms, TWA and STEL values, and time as well as temperature information.

### Calibration Cap & Smart Cap

Calibration and adjustment of the G222E are quite simple. All you need is the Calibration Cap for manual zero and test gas application.

If you want to read out the content of the data logger, you will need the Smart Cap, a USB connection cable and the Config Software for the G222 series instead.



*G222 with Calibration Cap.  
Alternatively available the  
Smart Cap with infrared  
interface and mini-USB plug.*



### Overview of the gases and measuring ranges

The smart sensors for the G222E are durable, easy to change and minimize operating costs. Sensors for the following gases are available for the G222E:

Gas	Formula	Measuring Range
Ammonia	NH <sub>3</sub>	0 to 200 ppm *
		0 to 300 ppm *
		0 to 1000 ppm *
Chlorine	Cl <sub>2</sub>	0 to 10 ppm *
Chlorine dioxide	ClO <sub>2</sub>	0 to 2 ppm
Hydrogen chloride	HCl	0 to 30 ppm *
Hydrogen cyanide	HCN	0 to 50 ppm *
Ethylene oxide	C <sub>2</sub> H <sub>4</sub> O	0 to 20 ppm *
Hydrogen fluoride	HF	0 to 10 ppm *
Carbon monoxide	CO	0 to 500 ppm *
Ozone	O <sub>3</sub>	0 to 1 ppm
Phosgene	COCl <sub>2</sub>	0 to 2 ppm
Phosphine	PH <sub>3</sub>	0 to 10 ppm *
Oxygen	O <sub>2</sub>	0 to 25 vol% (2 years)
		0 to 25 vol% (3 years)
		0 to 25 vol% (5 years)
Nitrogen dioxide	NO <sub>2</sub>	0 to 30 ppm *
Sulfur dioxide	SO <sub>2</sub>	0 to 10 ppm *
Hydrogen sulfide	H <sub>2</sub> S	0 to 100 ppm *
Silane	SiH <sub>4</sub>	0 to 20 ppm *
Nitric Oxide	NO	0 to 100 ppm *
tert-Butyl mercaptan (TBM)	C <sub>4</sub> H <sub>10</sub> S TBM	0 to 20 ppm *
Tetrahydrothiophene (THT)	C <sub>4</sub> H <sub>8</sub> S THT	0 to 20 ppm *
Hydrogen	H <sub>2</sub>	0 to 2000 ppm
		0 to 1 vol%
		0 to 4 vol%

\* Sensor can also be set to other measuring ranges (refer to sensor specification)



# Technical data: G222E

<b>Measuring principle:</b>	Electrochemical (EC) for toxic gases, hydrogen and oxygen
<b>Sample gas feed:</b>	Diffusion opening
<b>Display:</b>	2 x 4 digit LC display Indicates battery capacity and gas concentrations with unit
<b>Controls:</b>	2 operating buttons
<b>Alerting:</b>	2 very bright alarm LEDs, audible alarm and vibration alarm Depending on the gas type, 3 or 2 instantaneous alarms, battery alarm with visual and audible signaling and indication in the display Horn: 103 dB(A) (can be reduced to 90 dB(A))
<b>Zero point and sensitivity adjustment:</b>	Manual or automatic with adjustment program if necessary test gas supply via the "SMART CAP" with 0.5 to 0.6 slpm
<b>Power supply:</b>	Replaceable alkaline battery (1x AA) Replace only with battery listed in the operation manual!
<b>Battery life:</b>	Sensor dependent, per battery average: 9 months at 10 hour per working day or 90 days 24/7
<b>Climatic conditions:</b>	for operation: -4 to +122 °F / -20 to +50 °C   5 to 95% r.h.   70 to 130 kPa for storage: -13 to +131 °F / -25 to +55 °C   5 to 95% r.h.   70 to 130 kPa (recommended 0 to +30 °C)
<b>Housing:</b>	Rubberized polycarbonate / plastic
Material:	1.93 x 3.3 x 1.26 in / 49 x 84 x 32 mm (W x H x D)
Dimensions:	4.06 to 4.76 oz / 115 g to 135 g (with sensors, battery and clip)
Weight:	IP54
Protection class:	
<b>Approvals / Certifications:</b>	
Markings and type of protection:	G222E ⊗ II 1G Ex ia IIC T3 Ga      -20 °C ≤ Ta ≤ +55 °C ⊗ II 1G Ex ia IIC T4 Ga      -20 °C ≤ Ta ≤ +45 °C
EU type examination certificate:	BVS 18 ATEX E 027 X
IECEX Certificate of Conformity:	IECEX BVS 18.0020 X
Electromagnetic compatibility:	DIN EN 50270:2015 Interference emission: Type class I Interference immunity: Type class II



[www.gfgsafety.com/us-en](http://www.gfgsafety.com/us-en)

© GfG Instrumentation, Inc. 2022  
All specifications on this brochure are subject to technical changes due to further development.

USA and Canada  
Latin America  
Germany  
South Africa  
Asia Pacific  
Great Britain  
Switzerland  
France  
Poland  
Austria  
Netherlands

info@goodforgas.com  
info@goodforgas.com  
info@gfg-mbh.com  
info@gfg.co.za  
sales@gfg-asiapac.sg  
sales@gfggas.co.uk  
info@gfg.ch  
alainflachon@gfg-gasdetection.fr  
biuro@gfg.pl  
austria@gfg-mbh.com  
info@gfg-gasdetection.nl



GfG Instrumentation, Inc.  
1194 Oak Valley Drive, Suite 20, Ann Arbor, MI 48108 USA  
Phone: (734) 769-0573 • Toll Free (USA / Canada): (800) 959-0329  
Website: [www.gfgsafety.com/us-en](http://www.gfgsafety.com/us-en) • [info@goodforgas.com](mailto:info@goodforgas.com)

Rev. 2 (04/10/23)